

RAVEN RP500, RP510, RP520, RP530, RP540 Silicon weather stripping


RP500 (H)

Compression 1–3mm.

Reel Length 100m.

Colours RP500w (white), RP500b (brown), RP500blk (black)

Fixing 3 x 5.5mm deep kerf groove, push-in locking fit.




RP510 (H)

Compression 1–2mm.

Reel Length 100m.

Colours RP510w (white), RP510b (brown), RP510blk (black)

Fixing 3 x 5.5mm deep kerf groove, push-in locking fit.




RP520 (H)

Compression 1–3mm.

Reel Length 100m.

Colours RP520w (white), RP520b (brown), RP500blk (black)

Fixing 3 x 5.5mm deep kerf groove, push-in locking fit.




RP530 (H)

Compression 1–2mm.

Reel Length 50m.

Colours RP530w (white), RP530b (brown), RP500blk (black)

Fixing 4x 6mm deep kerf groove, push-in locking fit.




RP540 (H)

Compression 1–3mm.

Reel Length 100m.

Colours RP540bk (black)

Fixing 4 x 6mm deep kerf groove, push-in locking fit.



All to be used in conjunction Raven door bottom seals and threshold plates.



Royde & Tucker Ltd
 Bilton Road
 Cadwell lane
 Hitchin
 SG4 0SB
 Tel:01462 444444
 Fax:01462 444433
 www.ratman.co.uk
 e-mail: sales@ratman.co.uk